

USB rear mounting Socket



- **Removable USB socket module with special tool for quick and easy maintenance**
- **5 000 cycles of insertion/extraction**
- **0.5A to 2.4A per USB port**
- **USB type A or UBS type C compatible**

Standards:

- Product : EN62684, EN62680
- Application : EN50155
- EMC : EN50121-3-2
- Shock and vibration : EN61373
- Fire and Smoke : EN45545-2
- ROHS, REACH

Mechanical characteristics:

- Panel Rear mounting
- Insertion/extraction : 5 000 cycles
- Operating temperature: -25°C (-13°F) to + 55°C (+131°F)
- Removable USB type A 3.0 socket module with special tool for quick and easy maintenance
- Vandal proof mounting
- Single or Double, horizontal or vertical USB socket
- Marking of USB logo, voltage and Max current
- IP20, IK07

Electrical characteristics:

- 5VDC output according to USB standard
- Adjustable current limitation from 0.5A to 2.4A
- Railway power converter AC/DC or DC/DC in the range (not integrated in the USB socket)
- Spring terminal connection up to 1.5mm²(AWG16) for flexible conductor with ferrule

Mounting / Connection:

- Rear mounting with 2 screws M4 or n°8-32 UNC (Stud / nut compatible only for horizontal USB socket)
- Mechanical fixation of wires on the module with hose clamp

Options:

- Power supply indicator
- 2 USB ports with independent power supply
- Marking of voltage, current, power features
- Customization of front side colors

Labels : mm (in)

Schematics:

