



MAFELEC

BBE range

Creating control and signalling solutions for harsh environments



Simplified maintenance

The original box desing facilitates the access to auxiliaries and electronics.



Lighting characteristics:

- CMS LED
- Colors : green, red, amber
- Standard pictograms (other on request)
- Ring illuminated or not

Environmental characteristics

- Storage temperature - 40°C to +85°C
- Operating temperature - 40°C to +85°C
- Degree of protection IP 66, IK 08 per IEC & EN 60 529
- Fire resistance HB per UL94
- Vibrations resistance Per IEC & EN 60068-2-6

Design

- The particularly studied shape of these boxes integrates the protection of control and signalling auxiliaries like that of the pictograms.

Mounting

Projecting or flat



Option

- Marking of the pictograms directly on the push button heads (any pictograms available on request)



Equipment

- A range of boxes for 4, 5, 6, 8,10, or 12 auxiliaries Ø22 mm allowing of many configurations
 - Pushbuttons
 - Indicator lights
 - Selectors
 - Key switches
 - Joysticks
 - Emergency stop pushbuttons
- Special equipments on request.



AEROSPACE & DEFENCE



COACHES & BUSES



RAILWAY



INDUSTRY



ENERGY



PLEASURE BOAT



VERTICAL TRANSPORT



INDUSTRIAL VEHICLES



OFFSHORE & MINING

MAFELEC
www.mafelec.com

Textes et images non contractuels

(update 2017/06)